



1. CRIMPED FERRULE  
HEX CRIMP SIZE .128"
2. CRIMPED CONTACT PIN  
SQ. CRIMP SIZE 0.7mm
3. MAX. PANEL THICKNESS=5mm

RECOMMENDED  
CABLE STRIPPING DIM'S  
(建議剝線尺寸)

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)  
 1. BRASS  
 2. NICKEL PL. 100 MIN. THICK OVER COPPER PL. 50 MIN. THICK  
 3. PHOSPHOR BRONZE  
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK  
 OVER COPPER PL. 50 MIN. THICK  
 5. TEFLON

RoHS COMPLIANT

ISS	ZONE	REVISIONS			
ISS	ZONE	DESCRIPTION	PER REQUEST	DATE	

  

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
10	FERRULE	NOTE 1	NOTE 2	1	FR-32-39-95
9	CONTACT PIN	NOTE 1	NOTE 4	1	PIN-06-095-55
8	HEX NUT	NOTE 1	NOTE 2	1	HN-16-1228-28
7	LOCK WASHER	NOTE 1	NOTE 2	1	LW-13-16-05
6	GASKET	RUBBER	RED	1	GS-122-160-15
5	BARREL	NOTE 1	NOTE 2	1	71628-6421G4-5-02
4	CONTACT PIN	NOTE 3	NOTE 4	1	71628RP-6521G1-4
3	INSULATOR	NOTE 5	NATURAL	1	71628RP-6521G1-3-50T
2	BODY	NOTE 1	NOTE 2	1	71628RP-6121A1-2
1	HOUSING	NOTE 1	NOTE 2	1	71628RP-6421G4-1

DIMENSIONS ARE IN MILLIMETERS				PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				APPROVED	DATE
				CHECKED	DATE
				DRAWN	DATE
				SCALE	ISSUE
TITLE				TNC REVERSE BULKHEAD CRIMP JACK (FOR RG-316, 174, 188A, LMR100)	
DRAWING NO.				71628RP-6421G4-02-50	
FILE NO.				R:\D\G\DWG\71628\RP\6421G4\02\50-1	