

Technical Data Sheet

LMR-LW400-LSZH

Item no. 6067TM-LSZH-5

I. CONSTRUCTION

Center conductor: Solid Bare Copper Clad Aluminum	Diameter
Dielectric: Gas Injected Foam Polyethylene	.108 inches
Shield: Aluminum-Polyester-Aluminum-Adhesive Tape	.285
: 34 GA Aluminum Braid (90%k)	.291
Jacket: Black Low Smoke Low Toxicity Non-halogen FR Polyethylene	.320
PRINT: "LMR®-LW400-LSZH COAXIAL CABLE T TIMES MICROWAVE SYSTEMS	.405 +/- .015"
PH +1(203)949-8400 dmy ft"	

II. ENVIRONMENTAL and MECHANICAL PROPERTIES

Weight:	73.0 pounds per 1000 feet
Operating temperature:	-40°C to +85°C
Minimum bend radius:	1 inch
Flame & smoke:	see notes below

III. ELECTRICAL PROPERTIES

Impedance:	50 ohms
Capacitance:	23.9 pF per foot
Velocity:	85 %

Attenuation @	30 MHz:	0.7 dB per 100 feet
Typical (max)	50 MHz:	0.9 dB per 100 feet
	150 MHz:	1.5 dB per 100 feet
	220 MHz:	1.8 dB per 100 feet
	450 MHz:	2.7 dB per 100 feet
	900 MHz:	3.9 dB per 100 feet
	1500 MHz:	5.1 dB per 100 feet
	2000 MHz:	6.0 dB per 100 feet
	2500 MHz:	6.8 dB per 100 feet

Shielding: >90dB

IV. NOTES

1. Flame: Meets IEC-332-1-2, IEC 332-3 CAT.C, UL-VW1, UL-1581, IEE-383, BS-4066-1, BS-4066-3
2. Smoke: Meets IEC-61034-2, NES-711
3. Halogen: Meets IEC-60754-1, BS 6425-1, IEC-60754-2, BS 6425-2
4. MISC: Compliant to EN-45545 (R15/R16), DIN 5510-2, NF F16-101, BS-6853 Standards
5. UV Resistant: Meets UL-1581, 720 Hour UV Exposure
6. Meets NFPA-130 Requirements
7. ROHS Compliant: 2002/95/EC ROHS Directive and Amendment 2011/65/EC

This document contains Times Microwave Systems proprietary information. It shall not be duplicated, used or disclosed in whole or in part to third parties without written authorization from Times Microwave Systems. This data is EAR controlled IAW 15 CFR Part 730-774	Approvals				TIMES MICROWAVE SYSTEMS Wallingford, CT 06492 (203) 949-8400; (203) 949-8423.Fax		
	Drawn	EP	10/23/2016				
	CHK			LMR-LW400-LSZH			
	This Technical Specification is for Reference only						Size A
	45390				Scale: NA		Rev. (--A)