





Material	Plating (Micro-inch)
Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Teflon	
Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
	Brass Brass Beryllium Copper Teflon Brass

Weight:

Suitable Cables:RG174,RG188,RG316,RG316-E,RG316-FEP

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



## CABLE ASSEMBLY INSTRUCTION SSMC3100-0316 JYE BAO CO., LTD. С Α В **CONTACT PIN BODY FERRULE DIAGRAM** ASSEMBLY INSTRUCTION Step 1: STRIP AS SHOWN. 3.7 [.146] Step 2: SLIDE FERRULE " C " OVER CABLE. Step 3: PUT PIN " B " ON CENTER CONDUCTOR AND SOLDER IN " Y ". С Step 4: LOOSEN BRAIDING AND SLIDE CONNECTOR "A" IN PLACE. Step 5: SLIDE FERRULE " C " TOWARDS THE CONNECTOR " A " AND CRIMP. С

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.