





		1
Parts	Material	Plating (Micro-inch)
Ferrule	Brass	Gold 5 Over Nickel 50 Over Copper 50
Contact Pin	Brass	Gold 20 Over Nickel 50 Over Copper 50
Insulator	Teflon	
Body	Brass	Gold 5 Over Nickel 50 Over Copper 50
Barrel	Brass	Gold 5 Over Nickel 50 Over Copper 50

Weight: 2.09 g

Suitable Cables: RD316, RG316D-E, RD316-FEP, JBY100

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



## CABLE ASSEMBLY INSTRUCTION SMC8100D-0316 JYE BAO CO., LTD. В С Α **=** BODY **CONTACT PIN FERRULE** DIAGRAM ASSEMBLY INSTRUCTION 9.85 [.388] Step 1: STRIP AS SHOWN. Step 2: SLIDE FERRULE " C " OVER CABLE. Step 3: PUT PIN " B " ON CENTER CONDUCTOR AND SOLDER IN " Y ". Step 4: LOOSEN BRAIDING AND SLIDE CONNECTOR " A " IN PLACE. Step 5: SLIDE FERRULE " C " TOWARDS THE CONNECTOR " A " AND CRIMP.

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.