





Parts	Material	Plating (Micro-inch)
Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Washer	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Top Hat	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Gasket	Silicon	
Contact Pin	Brass	Gold 3 Over Nickel 50 Over Copper 50
Spring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Insulator	Teflon	
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50

Weight: 43.38 g

Suitable Cables: RG214

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



## CABLE ASSEMBLY INSTRUCTION TNC3200-0214 JYE BAO CO., LTD. С D Е G Α **BODY** CONTACT PIN TOP HAT **GASKET** WASHER NUT INSULATOR DIAGRAM ASSEMBLY INSTRUCTION Step 1: STRIP AS SHOWN. Step 2: SLIDE GASKET " D " , WASHER " E " AND NUT " F " OVER CABLE . 4.3 [.169] Step 3: WRAP THE BRAIDING BACKWARD OVER GASKET " D " Step 4: STRIP THE DIELECTRIC AS SHOWN. Step 5: SLIDETOP HAT " C " BETWEEN BRAIDING AND DIELECTRIC . Step 6: PUT CENTER PIN " B " ON CENTER CONDUCTOR . Step 7: SOLDER CENTER PIN IN " Y " . Step 8: SLIDE INSULATOR " G " INTO CONNECTOR BODY " A " . Step 9: FINALLY SCREW " F " ON THE CONNECTOR BODY " A " .

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.