



•		1
Parts	Material	Plating (Micro-inch)
Ferrule	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Retainer Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Gasket	Silicon	
Barrel	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Contact Pin	Brass	Gold 4 Over Nickel Phosphorous Alloy 80 Over Copper 20
Insulator	Teflon	
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50

Weight:

Suitable Cables: JBY300,5DFB

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



CABLE ASSEMBLY INSTRUCTION JYE BAO CO., LTD. TNC3100-L300 **TAIPEI TAIWAN R.O.C** В С Α **BODY CONTACT PIN FERRULE DIAGRAM** ASSEMBLY INSTRUCTION 17 [.669] Step 1: STRIP AS SHOWN. [.205] Step 2: SLIDE FERRULE " C " OVER CABLE. Step 3: PUT PIN " B " ON CENTER CONDUCTOR AND SOLDER IN " Y ". В Step 4: LOOSEN BRAIDING AND SLIDE CONNECTOR "A" IN PLACE. Step 5: SLIDE FERRULE " C " TOWARDS THE CONNECTOR "A " AND CRIMP.

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



CABLE ASSEMBLY INSTRUCTION JYE BAO CO., LTD. TNC3100-L300 **TAIPEI TAIWAN R.O.C** Α В С **BODY CONTACT PIN FERRULE** ASSEMBLY INSTRUCTION DIAGRAM 17 [.669] Step 1: STRIP AS SHOWN. 8 [.315] [.205] Step 2: SLIDE FERRULE " C " OVER CABLE. Step 3: PUT PIN " B " ON CENTER CONDUCTOR AND SOLDER IN " Y ". Step 4: LOOSEN BRAIDING AND SLIDE CONNECTOR " A " IN PLACE. Step 5: SLIDE FERRULE " C " TOWARDS THE CONNECTOR " A " AND CRIMP.

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.