



| Parts | Material | Plating(Micro-inch) |
|--------------|-----------------|------------------------------------------|
| Ferrule | Brass | Tin-Zinc-Copper-Alloy 100 Over Copper 50 |
| Contact Pin | Phosphor Bronze | Gold 3 Over Nickel 50 Over Copper 50 |
| Contact Body | Brass | Tin-Zinc-Copper-Alloy 100 Over Copper 50 |
| Spring | Brass | Tin-Zinc-Copper-Alloy 100 Over Copper 50 |
| Gasket | Silicon | |
| Insulator | Teflon | |
| Body | Brass | Tin-Zinc-Copper-Alloy 100 Over Copper 50 |
| Coupling Nut | Brass | Tin-Zinc-Copper-Alloy 100 Over Copper 50 |

Weight: 15.77 g

Suitable Cables: LMR240, JBY240

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



CABLE ASSEMBLY INSTRUCTION JYE BAO CO., LTD. TNC6100-L240 **TAIPEI TAIWAN R.O.C** С В Α - 0 CONTACT PIN **FERRULE BODY** DIAGRAM ASSEMBLY INSTRUCTION 16 [.630] Step 1: STRIP AS SHOWN. 7.1 [.280] 3.5 [.138] Step 2: SLIDE FERRULE " C " OVER CABLE. Step 3: PUT PIN " B " ON CENTER CONDUCTOR AND SOLDER IN " Y ". С В Step 4: LOOSEN BRAIDING AND SLIDE CONNECTOR " A " С Step 5: SLIDE FERRULE " C " TOWARDS THE CONNECTOR С " A " AND CRIMP.

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.