



TECHNICAL DATA SHEET

50 ohm Connectors for Radiating Cables

Kabelwerk

EUPEN AG

Rev.: 07/2011-12-01

cable

Connectors for LSC/RMC 1/2", 5/8", 7/8" radiating cables

FEATURES

- **High contact force and inner contacts made in a high-strength copper alloy**
- **Silver plated**
- **Watertight (IP67/IP68)**
- **Corrosion resistant**
- **Quick trimming tool**
- **Installation "fit on and tighten it"**



The connectors are designed according the standard interfaces as N or DIN 7-16. Contact components are silver plated to minimize insertion loss; mechanical parts are nickel plated for heavy-duty handling and best corrosion resistance. The special quick trimming tool make installation very easy and cost effective in time.

SPECIFICATIONS

Connector type	N-male	N-female	7-16 male	7-16 female
Electrical specifications				
• Nominal impedance [Ω]			50	
• Reflection coefficient @ 3 GHz [dB]			≥ 35	
• Insulation resistance [$G\Omega$]	≥ 5			≥ 10
• Test voltage (at sea level) [kV rms, 50Hz]	2.5			4
• Working voltage (at sea level) [kV rms,50Hz]	1			2.7
• Contact resistance (outer contact) [$m\Omega$]		≤ 2		
• Contact resistance (inner contact) [$m\Omega$]		≤ 2		
Mechanical specifications				
• Torque of coupling mechanism [Nm]	8			30
• Tensile strength of coupling mechanism [N]	400			1000
• Cable retention [N]	> 500			> 1000
• Mechanical endurance (Nr of couplings)		≥ 500		
Environmental specifications				
• Temperature range	-40 °C to +85 °C (-40 °F to +185 °F)			
• Degree of protection	IP67/IP68 (mated connectors)			
Materials				
• Externals parts	Passivated silver plated or electroless nickel plated brass			
• Outer contact	Passivated silver plated brass			
• Inner contact	Passivated silver plated high-strength copper alloy and brass			
• Dielectric	PTFE and (or) TPX			
• Gaskets	High quality silicone & nitrile			
Tool codes				
• 1/2"			SPTC50R12	
• 5/8"			SPTC50R58	
• 7/8"			SPTC50R78	
Connectors codes				
• 1/2"	NM50R12	NF50R12	-	716FR12
• 5/8"	NM50R58	NF50R58	-	-
• 7/8"	NM50R78	NF50R78	-	716FR78



INSTALLATION INSTRUCTIONS CONNECTORS for Radiating Cables

Kabelwerk **EUPEN** AG

E0012 Rev.06/2016-11-25 cable

Connectors for 1/2" Radiating Cables



3M : F 04/013
Abrasive
Abratif
Schleifmittel
Schnuurspons
Abrasivo
磨砂纸











or



	NF, 7-16F	NM	7-16M
	2 x 22 mm	2 x 22 mm & 19 mm	2 x 22 mm & 32 mm



Cable preparation tool
SPTC50R12



For any questions please contact KABELWERK EUPEN AG / for US Customer service call 1-800-419-5100

(D) Verarbeitung nur durch eine Elektrofachkraft.
Es besteht die Gefahr eines elektrischen Schlags!

(F) Installation uniquement par une personne qualifiée en électricité.
Il y a un risque de choc électrique!



(NL) Installatie alleen door een vakman voor elektriciteit.
Er is gevaar van elektrische schok!

(GB) Processing only by a qualified electrician.
There is a risk of electric shock!

NOTICE:
KABELWERK EUPEN AG
disclaims any liability or
responsibility for the results
of improper or unsafe installation
practices.

AVIS:
KABELWERK EUPEN AG
décline toute responsabilité
en cas de non respect de
ces instructions.

WAARSCHUWING:
KABELWERK EUPEN AG
wijst elke verantwoordelijkheid
van de hand in geval
van het niet opvolgen van
deze aanbevelingen.

BEMERKUNG:
KABELWERK EUPEN AG
lehnt jede Verantwortung bei
Nichtbeachtung dieser
Instruktionen ab.

AVISO:
KABELWERK EUPEN AG
rehusa todas las responsabilidades
en caso de no
respetar las instrucciones.

注意:
本公司对于不恰当或不
安全的安装, 检修或拆
卸操作所导致的结果不任
何义务和责任。