

GP 80 B/

Broad-Banded, Antistatic Ground-Plane Antenna for the 80 MHz Band

- GP 80 B/ is a broad-banded ground-plane antenna of the triple-leg type.

DESCRIPTION

- The 80 MHz-band is covered by 3 models covering the following frequency segments: 66 - 78 MHz, 71 - 83 MHz and 76 - 88 MHz.
- Atmospherical discharges are immediately led to ground, as all metal parts are DC-connected. Consequently, the antenna shows a DC-short across the coaxial cable.
- GP 80 B/... is made from corrosion-resistant aluminium, which together with a special anodizing process gives this antenna a very long lifetime.
- LW-SS-1" mounting bracket and GP Adapor is available as accessories.

SPECIFICATIONS

ELECTRICAL	
MODEL	GP 80 B/
ANTENNA TYPE	¼ λ ground-plane, broad-banded
FREQUENCY	Models within 66 - 88 MHz (see model survey)
IMPEDANCE	Nom. 50 Ω
RADIATION	Omnidirectional
POLARIZATION	Vertical
GAIN	2 dBi0 dBd
BANDWIDTH	12 MHz
SWR	≤ 1.6
MAX. POWER	600 W
ANTISTATIC PROTECTION	All metal parts DC-grounded (Connector shows a DC-short)
MECHANICAL	
CONNECTOR	0.5 m tail of RG 213 terminated with an N-female connector
WIND SURFACE	0.101 m²
WIND LOAD	128 N @ 160 km/h
COLOUR	Black
MATERIALS	Black anodized, corrosion-resistant aluminium



ORDERING DESIGNATIONS

TYPE	FREQUENCY	PRODUCT NO.
GP 80 B/l	66 - 78 MHz	100000065
GP 80 B/m	71 - 83 MHz	100000064
GP 80 B/h	76 - 88 MHz	100000063
ACCESSORIES		PRODUCT NO.
LW-SS-1"		110000394
GP Adaptor		100000679

TYPICAL SWR - CURVE

