

Rubber Antenna for ICOM Portable Equipment in the 70 cm Band

DESCRIPTION

- Sturdy, conical, flexible rubber antenna.
- Highest quality materials – designed for “wear and tear”.
- Full-size ¼ λ whip.
- Delivered factory tuned and tested to ensure minimum SWR.
- Especially designed for ICOM IC-F61 (450 MHz band).

SPECIFICATIONS

Electrical	
Model	GA 70/...-IC-F61
Frequency	70 cm band covered by three models
Antenna Type	Antenna for portable equipment
Polarisation	Vertical
Impedance	50 Ω
Gain	0 dB (compared to a ¼ λ portable antenna)
Maximum Input Power	100 W

Mechanical	
Connection(s)	SMA (male) special for IC-F61
Materials	Steelwire moulded in thermoplastic rubber Environment-proof plastics Black-chromed brass
Colour	Black
Height	140 mm / 5.51 in.
Weight	0.03 kg / 0.07 lb

ORDERING

Type	Product No.	Frequency
GA 70/s-IC-F61	140000189	380 - 430 MHz
GA 70/h-IC-F61	140000191	420 - 470 MHz
GA 70/l-IC-F61	140000193	400 - 450 MHz



DIAGRAM

TYPICAL SWR CURVE

