

Flexible Antenna for ICOM Portable Equipment in the 70 cm Band

DESCRIPTION

- > Flexible antenna made of steel wire covered with silicone tube.
- > Full-size $\frac{1}{4} \lambda$ whip.
- > Highest quality materials.
- > Delivered factory tuned and tested to ensure minimum SWR.
- > Especially designed for ICOM IC-F61 (450 MHz band).

SPECIFICATIONS

Electrical	
Model	FLX 70/...-IC-F61
Frequency	70 cm band covered by three models
Antenna Type	Antenna for portable equipment
Polarisation	Vertical
Impedance	50 Ω
Gain	0 dB (compared to a $\frac{1}{4} \lambda$ portable antenna)
VSWR	< 2.0:1 when mounted directly on portable equipment
Maximum Input Power	200 W

Mechanical	
Connection(s)	SMA (male) special for IC-F61
Materials	Silicone tube over steel wire Weather- and shockproof plastics Black-chromed brass
Colour	Black
Height	200 mm / 7.87 in.
Weight	0.025 kg / 0.06 lb

ORDERING

Type	Product No.	Frequency
FLX 70/s-IC-F61	140000168	380 - 430 MHz
FLX 70/l-IC-F61	140000376	400 - 450 MHz
FLX 70/h-IC-F61	140000167	420 - 470 MHz



DIAGRAM

TYPICAL SWR CURVE

