

6 dBd Omdirectional Base Station and Marine Antenna for the 1800 MHz Band

DESCRIPTION

- Vertically polarized, omnidirectional base station and marine antenna.
- Approximately 6 dBd gain.
- Simple mounting using the 1" revolving nut system.
- Wide variety of accessory mounting brackets available.
- Large bandwidth with respect to both SWR and gain. Highly suitable for duplex operation with large spacing between the TX and the RX frequencies, e.g. the DCS-1800/PCN cellular system.
- The antenna element is sealed in a high-quality, conical glass fibre tube.
- All metal parts in the antenna are DC-grounded to reduce the noise caused by atmospherical discharge. Consequently, the antenna shows a DC-short across the
- The CXL 1800-6 is a vibration-proof, lightweight, slim-line, corrosion resistant, modern style base station and marine antenna.

SPECIFICATIONS

Electrical	
Model	CXL 1800-6
Frequency	1700 - 1900 MHz
Antenna Type	Collinear, broad-band
3 dB Beamwidth, H-Plane	Omnidirectional
Polarisation	Vertical
3 dB Beamwidth, E-Plane	14 °
Impedance	50 Ω
Gain	6 dBd (8.2 dBi)
Maximum Input Power	100 W
Antistatic Protection	All metal parts DC-grounded (Connector shows a DC-short)
HCM Code(s)	

Mechanical	
Wind Area	0.03 sq. m / 0.32 sq. ft
Connection(s)	N(f)
Materials	Shroud: Polyurethane-coated glass fibre Mounting bracket: Chromed brass
Colour	White (RAL 9003)
Height	1150 mm / 45.28 in.
Wind Load	38 N (160km/h)
Dia. At Top End	21 mm / 0.83 in.
Weight	0.7 kg / 1.54 lb
Dia. At Bottom End	23 mm / 0.91 in.
Mounting	On 1" RG (G1" - 11) threaded water pipe or on optional mounting brackets (see accessories)

Environmental	
Operating Temperature Range	-30°C to +70°C

ORDERING


Туре	Product No.
CXL 1800-6	100000186




DIAGRAM

TYPICAL GAIN AND SWR CURVES

TYPICAL RADIATION PATTERN (E-PLANE)





TYPICAL RADIATION PATTERN (H-PLANE) ACCESSORIES (to be ordered separately)

