

colinear 2 dB Mobile Magnetic Antenna for the UMTS Band

DESCRIPTION

- Mobile magnetic antenna for the UMTS band (1900 2200 MHz). Colinear, stainless steel whip.
- > 2 dB gain compared to a ¼ λ whip.
- Stainless steel MMS-mount professional quality in elegant and smooth design.
- > Low profile magnetic mount.
- > Provided with FME-connection (supplied without cable).
- Silicone layer on contact surface protects the car roof and ensures maximum friction.



ORDERING

Туре	Product No.
MU 2404/UMTS-MMS	130001279

SPECIFICATIONS

Electrical		
Model	MU 2404/UMTS-MMS	
Frequency	UMTS band (1900-2200 MHz)	
Antenna Type	Colinear magnetic mobile whip antenna	
Polarisation	Vertical	
Impedance	50 Ω	
VSWR	< 2.0 @ f.res.	
Maximum Input Power	25 W	
Bandwidth	> 200 MHz @ SWR < 2.25	
Gain (EIA RS-329-1)	2 dB	

vlechanical		
Materials	Whip: Black-chromed, stainless steel, Black-chromed brass Mount: Black-chromed brass and steel Silicone layer on contact surface All materials are chosen to avoid corrosion	
Cable	FME-cable to be ordered separately	
Colour	Black	
Height	190 mm / 7.48 in.	
Weight	0.255 kg / 0.56 lb	
Mounting	Centre of vehicle roof for best omnidirectional coverage	
Maximum Car Speed	170 km/h	



ADDITIONAL DATA


INSTALLATION


The MU 2404/UMTS-MMS should be mounted at the centre of the vehicle roof to ensure best omnidirectional coverage

The MMS-mount is especially suited for temporary antenna installations where it is not desirable to drill a hole in the vehicle. The magnetic mount can advantageously serve several vehicles by shifting it from one vehicle to another. The MMS-mount is provided with a thoroughly magnetized permanent ring magnet positioned in a carefully shaped magnetic circuit which yields an extraordinarily high attaching effect and makes this mount stand for very high values of bending moment and mechanical shock.

A silicone layer applied to the contact surface protects the car roof and ensures maximum friction.

INSTALLATION DIMENSIONS





TUNING

The antenna is delivered factory-tuned and requires no further tuning.

PLEASE NOTE

For safety reasons:

When using the MU 2404/UMTS-MMS car speed must not exceed 170 km/h.