

Attenuator 100 W

DESCRIPTION

- This series includes 3 dB, 6 dB, 10 dB, 20 dB and 30 dB attenuators.
- This series of attenuators has very low SWR and attenuation flatness and is especially suitable for use with:
 - Coaxial Transmission Lines
 - Power Monitors
 - Watt Meters
- The attenuators have a finish of black anodization.



ORDERING

Type	Product No.
PRO-ATT 3 dB-100-3-N(f)	200001731
PRO-ATT 6 dB-100-3-N(f)	200001757
PRO-ATT 10 dB-100-3-N(f)	200001758
PRO-ATT 20 dB-100-3-N(f)	200001743
PRO-ATT 30 dB-100-3-N(f)	200001742
PRO-ATT 3 dB-100-3-7/16(f)	200002509
PRO-ATT 6 dB-100-3-7/16(f)	200002538
PRO-ATT 10 dB-100-3-7/16(f)	200002510
PRO-ATT 20 dB-100-3-7/16(f)	200002539
PRO-ATT 30 dB-100-3-7/16(f)	200002540

SPECIFICATIONS

Electrical	
Model	PRO-ATT ... dB-100-3
Frequency	DC - 3 GHz
Impedance	50 Ω
Attenuation	See table below
VSWR	< 1.25:1
Mechanical	
Connection(s)	N female or 7/16 female
Dimensions	152 x 120 x 120 mm / 5.98 x 4.72 x 4.72"
Weight	2.5 kg / 5.51 lb
Environmental	
Operating Temperature Range	-35°C to +70°C

ADDITIONAL DATA

MODEL	ATTENUATION	ATT. DEVIATION	
		DC - 2.0 GHz	2.0 - 3.0 GHz
PRO-ATT 3 dB-100-3	3 dB	+/-0.5 dB	+/-0.75 dB
PRO-ATT 6 dB-100-3	6 dB	+/-0.5 dB	+/-1.0 dB
PRO-ATT 10 dB-100-3	10 dB	+/-0.75 dB	+/-1.5 dB
PRO-ATT 20 dB-100-3	20 dB	+/-0.75 dB	+/-1.5 dB
PRO-ATT 30 dB-100-3	30 dB	+/-0.75 dB	+/-1.5 dB

