

2-Channel 19" 3 HU Single Tray Combining System

DESCRIPTION

- An integrated single tray combining solution housing a 2-channel hybrid TX hybrid combiner, duplex filter, active RX multicouplers and preselector.
- Minimal rack space required - only 3 HU.
- Compatible with digital 6.25 kHz channel spacing.
- Single TX isolators fitted as standard (dual isolators available as option).
- 2 RX ports as standard (4 ports available as option).
- Please specify TX / RX frequencies when ordering.



ORDERING

Type	Product No.
PRO-COM450-HDAR-2/l	210001739
PRO-COM450-HDAR-2/h	210001738
PRO-COM450-BHDAR-2/l (With black front plate)	210002344
PRO-COM450-BHDAR-2/h (With black front plate)	210002345
ADAPTOR AC/DC 12V EU	240000040
ADAPTOR AC/DC 12V UK	240000041

SPECIFICATIONS

Electrical	
Model	PRO-COM450-HDAR-2/...
Frequency	l: 340 - 400 MHz h: 406 - 470 MHz
Maximum Tx-Tx Spacing	2 MHz
Minimum Duplex Spacing	5 MHz
Insertion Loss Tx Path	< 5.0 dB
Impedance	50 Ω
Ant-Tx Isolation	> 40 dB @ 25° C
Rx-Rx Isolation	> 20 dB
Tx-Tx Isolation	> 70 dB
VSWR	< 1.5:1
Maximum Input Power	35 W
LNA Noise Figure	< 3.5 dB
Current Consumption	500 mA @ 12 VDC
Rx Gain	1 dB +/- 1 dB (factory set)
No. Of Channels	2

Mechanical	
Input Connection(s)	N(f)
Dimensions	19" x 3 HU x 400 mm (483 x 133 x 400 mm)
Weight	6.3 kg / 13.89 lb

Environmental	
Operating Temperature Range	-30°C to +60°C

ADDITIONAL DATA


ADAPTOR AC/DC 12V EU



ADAPTOR AC/DC 12V UK



MOUNTING



All dimensions are given in mm [in.].

EU DECLARATION OF CONFORMITY

Hereby Amphenol Procom declare that the product type PRO-COM450-HDAR-2/... is in compliance with EU Directive 2014/53/EU.

The full text of the EU Declaration of Conformity is available at:

</images/shop/catalog/pdf-for-catalouges/Declaration-of-Conformity-PRO-COM-HDAR.pdf>