

Wideband Ground-Air omni, 3 dBd, 108-175MHz

DESCRIPTION

The 470 Series of glassfibre omni antennas are designed for wide band, particularly military and ground-to-air applications. The antennas are well suited to the most demanding applications both physically and environmentally, and have been engineered for optimal performance over a bandwidth greater than 50% of their centre frequency. Available in single dipole, multidipole and colinear versions.

- Former Skymasts brand product.

SPECIFICATIONS

Electrical	
Frequency	108 - 175 MHz
Max. Input Power	500 W
Omni Deviation	< ± 1 dB
Polarisation	Vertical
3 dB Beamwidth, E-Plane	40 °
3 dB Beamwidth, H-Plane	Omnidirectional
Impedance	50 Ω
Gain	3 dBd (5.2 dBi)
VSWR	< 2.0:1
Antistatic Protection	All metal parts DC-grounded (Connector shows a DC-short)
Mechanical	
Radiating Element(s)	120mm dia. aluminium tube
Connection(s)	N(f)
Radiator Feed	PTFE dielectric coaxial cable
Radome Material / Colour	GRP tube dark green, 128mm dia.
Length	3400 mm / 133.86 in.
Wind Area	0.522 sq. m / 5.62 sq. ft
Wind Load	648 N (160km/h)
Weight	18 kg / 39.68 lb
Mounting	Flanged base with six M14 fixing holes on 190 mm PCD
Environmental	
Survival Wind Speed	270 km/h


ORDERING

Type	Product No.	Frequency
Wideband Ground-Air omni, 3 dBd, 108-175MHz	470.31.05.00	108 - 175 MHz



DIAGRAM

RADIATION PATTERNS



MOUNTING & DIAGRAMS



RADIATION PATTERNS

