

# HD-142/144

## HDMI-splitter 1x2 och 1x4



Art. nr: **380 00 61** | HDMI-splitter HD-144, 1x4, V 1.4, 1080p, 3D, 4Kx2K | E-nr: 60 003 55  
 Art. nr: **380 00 63** | HDMI-splitter HD-142, 1x2, V 1.4, 1080p, 3D, 4Kx2K | E-nr: 60 004 30  
 Art. nr: **380 00 64** | HDMI-splitter HD-142-4K, 1x2, V1.4, 1080p+upscaling, 3D, 4Kx2K | E-nr: –

HDMI splitter fördelar en HDMI-källa till två eller fyra HDMI-signaler simultant. Dessa HDMI-fördelare stöder alla obligatoriska och flera valfria 3D-format, som beskrivs i HDMI 1.4 specifikationen. Stöder HD-upplösning: 4Kx2K @24 Hz, 1080p @60 Hz, 720p/1080i @120Hz. Stöder digitala ljudformat, exempelvis High Definition Audio support: Dolby TrueHD, och DTS-HD Master Audio. HD-142-4K skalar även upp en 1080 signal till 4K.

### Technical data

Operating Temperature Range	-5 to +35°C (+23 to +95°F)
Operating Humidity Range	5 to 90% RH (No Condensation)
Input Video Signal	0.5–1.0 Volts P-P
Input DDC Signal	5 volts P-P (TTL)
Data transfer speed rate	6.75 Gbps (Maximum)
Video Format Supported	DTV/HDTV: 480i/576i/480P/576P/720P/1080i/1080P/4Kx2K, 3D video support
HDMI Output	HDMI 1.4 + HDCP 1.1
Support Video Color Format	xv-YCC/deep color 36bit
Support Audio Format	DTS-HD/true-HD/LPCM7.1/AC3/DTS/DSD
Power consumption	<b>HD-144:</b> 10 W (Max) / <b>HD-142:</b> 3 watts (Max)
Dimension (LxWxH)	<b>HD-144:</b> 115x62x25 mm / <b>HD-142:</b> 75x68x25,2
Net Weight	210 g